



**FROM OUNCES TO TONS**  
NO JOB TOO BIG OR TOO SMALL

23 Chapple Street, Hamilton, Ontario, L8L 8K7

Toll free 866 979 7911 Phone 905 297 7911 Fax 905 385 2614

E-mail [info@alchemyextrusions.com](mailto:info@alchemyextrusions.com)

## Sheet Lead - For Shielding Applications

### ***What we can do:***

- 1/64 " to 1" Thick (See chart below)
- Standard roll = 4' x 10' and 3' x 18'
- Standard roll for 1/64" = 3' x 12'
- Any sizes of cut pieces available

### ***The benefits:***

- Manufactured from refined pure leads and a variety of special alloys upon request. Conforms to ASTM B-29, B-749 and Federal QQ-L-201F, QQ-L-171E.
- Many applications including; nuclear shielding, tank linings, roof flashing, sound-proofing, vibration absorbers, waterproofing and x-ray shielding.

### ***Thicknesses and Weights for Standard Sizes***

Actual Fraction	Approx Lbs/Ft <sup>2</sup>	Approx. Thickness	Actual Metric (mm)	Approx. Kg/M <sup>2</sup>	Standard Roll Size	Standard Roll Weight
1/64	1#		0.4	4.88	3 Ft x 12 Ft	40
1/32	2#		0.8	9.76	4 Ft x 10 Ft	80
1/16	4#		1.6	19.52	4 Ft x 10 Ft	160
3/32	6#		2.4	29.28	4 Ft x 10 Ft	240
1/8	8#		3.2	39.04	4 Ft x 10 Ft	320
1/4	16#		6.4	78.08	4 Ft x 10 Ft	640
1/2	30#		12.7	146.40	4 Ft x 10 Ft	1200
3/4	45#		19.1	219.60	4 Ft x 10 Ft	1800
1	60#		25.4	292.80	4 Ft x 10 Ft	2400

**Custom Sizes, Pieces, Rolls, etc... To your Specifications**